

IN THE CLAIMS:

The status of the claims is as follows:

5

1 – 10 (Cancelled)

11. (Currently Amended) An audio boost circuit comprising:

- an input buffer coupled to be responsive to a program input signal having
 10 high, low and mid-range frequency signal components, the input buffer having a state-
 variable filter for processing the program input signal into high, low and mid-range
 frequency signal components, and a state-variable summing amplifier for balancing and
 summing the low range, high range and mid-range signal components and for providing
 [[the]] a buffered program signal,
 15 an all pass phase inverter having an input coupled to receive the buffered
 program signal and an output providing an inverted buffered program signal,
 a Band-pass filter having a predetermined Q, [[responsive]] coupled to
receive the buffered program signal [[for providing]] and to provide an inverted Band-pass
 boosted program signal,
 20 a summing amplifier for adding the inverted buffered program signal to the
 inverted Band-pass boosted program signal and for providing a composite output signal.

12. (Currently Amended) The audio boost circuit of claim 11 wherein the input
 buffer's state-variable filter for providing a compensated signal further comprises:

- 25 a first amplifier stage responsive to the program signal for providing a high
range frequency compensated signal;
 a second amplifier stage responsive to an output of the first amplifier stage
 for providing a mid-range frequency compensated signal;
 a third amplifier stage responsive to the mid range compensated signal for
 30 providing a low range frequency compensated signal; and
 a state-variable summing circuit for adding the high range frequency
 compensated signal, the low range frequency compensated signal and the mid-range
frequency compensated signal to provide the buffered program signal.

13. **(Currently Amended)** The audio boost circuit of claim 12 wherein the mid-range frequency compensated signal is out of phase with the high range frequency compensated signal and low range frequency compensated signals.

5

14. **(Currently Amended)** The audio boost circuit of claim 13 wherein the input buffer's state-variable filter for providing a buffered program signal further comprises:

an adjusting means for adjusting the gain between the high range frequency compensated signal and the mid-range frequency compensated signal.

10

15. **(Currently Amended)** An audio boost circuit comprising:

an input buffer responsive to a program input signal having high, low and mid-range frequency signal components for providing a buffered program signal, the input buffer comprising:

15

a state-variable filter for processing the input program signal into high range, low range and mid-range frequency compensated signal components, the state-variable filter comprising:

a first amplifier stage responsive to the program signal for providing a high range frequency compensated signal;

20

a second amplifier stage responsive to an output of the first amplifier stage for providing a mid-range frequency compensated signal; and,

a third amplifier stage responsive to an output of the second amplifier stage for providing a low range frequency compensated signal;

the input buffer further comprising:

25

a state-variable summing circuit for adding the high range frequency compensated signal, the low range frequency compensated signal and the mid-range frequency compensated signal and an adjusting means for adjusting the gain between the high range frequency compensated signal and the mid-range frequency compensated signal; and the low range frequency compensated signal to provide the buffered program signal;

30

an all pass phase inverter having an input coupled to receive the buffered program signal and an output providing an inverted buffered program signal,

a Band-pass filter having a predetermined Q, responsive to the buffered program signal for providing an inverted Band-pass boosted program signal,

a summing amplifier for adding the inverted buffered program signal to the inverted Band-pass boosted program signal and for providing a composite program signal, and

5 a power amplifier and speaker means responsive to the composite program signal for producing an audible sound in response to the composite program signal.

16. **(Currently Amended)** The audio boost circuit of claim 15 wherein the mid-range signal components are inverted in phase with respect to the high and low range frequency signal components.

10

17. **(Currently Amended)** The audio boost circuit of claim 15 wherein the input buffer's state-variable filter further comprises:

a first amplifier stage having an inverting and non-inverting input; the program signal being coupled to the inverting input; and

15

a resistor divider network responsive to the mid-range compensated signal, the resistor divider network having an output for providing a portion of the mid-range frequency compensated signal to the first amplifier non-inverting input.

18 **(Currently Amended)**..An audio boost circuit comprising:

20

an input buffer means [[connected to receive the]] for receiving a program input signal and for processing the input program signal to provide high, low and mid-range frequency compensated signal components, the input buffer having gain control circuitry for balancing and summing the high and mid-range frequency compensated signals,

25

an all pass phase inverter having an input coupled to receive the buffered program signal and an output providing an inverted buffered program signal,

a Band-pass filter having a predetermined Q, responsive to the buffered program signal for providing an inverted Band-pass boosted program signal,

30

a summing amplifier for adding the inverted buffered program signal to the inverted Band-pass boosted program signal and for providing a composite program signal.

19. (Withdrawn)..The audio boost circuit of claim 18 wherein the Band-pass filter having a predetermined Q has a peak gain at a center frequency, and,
frequency adjustment means for adjusting the frequency at which the peak gain occurs.

5

20. (currently amended)..The audio boost circuit of claim [[2]] 18 wherein the Band-pass filter having a predetermined Q further comprises:

a first, second and third resistor, each having a first and second terminal,
a first and second capacitor, each capacitor having a first and second
10 terminal, and
an operational amplifier having an inverting input, a non-inverting input and an output,
the first resistor first terminal being coupled to receive the buffered program signal, the first resistor second terminal being coupled to the second resistor first
15 terminal and to the first terminal of the first and second capacitors, the second resistor's second terminal being coupled to a reference potential and to the operational amplifier's non-inverting input, the first capacitor second terminal being connected to the operational amplifier's inverting input and to the third ~~[[resistors]]~~ resistor's first terminal, the second capacitor's second terminal being connected to the operational amplifier's output terminal
20 and to the third resistor's second terminal.

21. (Withdrawn)..The audio boost circuit of claim 19 wherein the Band-pass filter frequency adjustment means for adjusting the frequency at which the peak gain occurs comprises:

25 a frequency adjustment resistor interposed in series with the second resistor and the reference potential.

22. (Withdrawn)..The audio boost circuit of claim 21 wherein the Band-pass filter's first, second and third resistor values and the values of the first and second
30 capacitors are selected to obtain a Q in the range of from 3 to 6, and

the frequency adjustment resistor is adjusted to position the peak gain at a frequency in the range of 50 to 100 hertz

23. **(Withdrawn)**..The audio boost circuit of claim 18 wherein the summing amplifier for adding the inverted buffered program signal to the inverted Band-pass boosted program signal and for providing a composite program signal further comprises:

- 5 a first input coupled to receive the inverted buffered program signal and a second input coupled to receive the inverted Band-pass boosted program signal, and adjustment means for adjusting the relative gain of the inverted buffered program signal with respect to the inverted Band-pass boosted program signal.

24. **(Withdrawn)**..The audio boost circuit of claim 23 wherein the adjustment means for adjusting the relative gain of the inverted buffered program signal with respect to the inverted Band-pass boosted program signal further comprises a boost adjusting resistor in series with the second input to the summing amplifier.

25. **(currently amended)**..The audio boost circuit of claim 18 wherein the input buffer further comprises:

a state-variable filter responsive to the program input signal for producing high, low and mid-range frequency compensated signal components; and

a state-variable summing amplifier for adding the high, low and mid-range frequency compensated signal components to provide the buffered program signal.

20

26. **(currently amended)**..The audio boost circuit of claim [[26]] 25 wherein the mid-range signal components produced by the state-variable filter are inverted in phase with respect to the phase of the high and low frequency compensated signal components produced by the state-variable filter .

25